

CLAIMS

1. A method of forming a two dimensional map of a three dimensional environment, there being a map origin located in the three dimensional environment, a viewing
5 direction vector defined passing through the map origin, and a one-to-one correspondence between map positions in the map and the directions of vectors passing through the map origin;

the method comprising the steps of:

10 associating an environment position in the three dimensional environment with a folded vector that passes through the map origin, the folded vector lying in a plane containing both the viewing direction vector and the environment position and forming an angle with the viewing direction vector that is a predetermined function of the angle between the viewing direction vector and a vector between the map origin and the environment position;

15 associating an environment position with the map position corresponding to the direction of the folded vector associated with that environment position; and

deriving properties for a map position from the properties of the corresponding environment position.

20 2. A method according to claim 1, in which the predetermined function is a multiplication by a predetermined quantity.

3. A method according to claim 2, in which the predetermined function is a multiplication by 0.5.

25

4. A method according to any one of the preceding claims, in which the one-to-one correspondence of a map point with the direction of a vector through the map origin represents a projection onto a predetermined plane of a point on the vector which is a predetermined distance from the map origin.

30

5. A method according to claim 4, in which the predetermined plane is a plane orthogonal to the viewing direction vector.

6. An image rendering method comprising the steps of:
generating a two dimensional map of a three dimensional environment using a
method according to any one of the preceding claims;
for a point of interest on an object to be displayed, deriving a reflection vector in
dependence on a normal vector at the point of interest and a direction of view;
referencing a position in the two dimensional map using the reflection vector, to
detect environmental properties at that map position; and
varying the appearance of the object at the point of interest in dependence on the
detected environmental properties.
7. A method according to claim 6, in which the varying step is performed in
dependence on a reflectivity of the object at the point of interest.
8. A method according to claim 6 or claim 7, in which the environmental properties
represent lighting properties.
9. Computer software having program code for carrying out a method according to
any one of the preceding claims.
10. A providing medium by which software according to claim 9 is provided.
11. A medium according to claim 10, the medium being a transmission medium.
12. A medium according to claim 10, the medium being a storage medium.
13. Apparatus for forming a two dimensional map of a three dimensional
environment, there being a map origin located in the three dimensional environment, a
viewing direction vector defined passing through the map origin, and a one-to-one
correspondence between map positions in the map and the directions of vectors passing
through the map origin;
the apparatus comprising:
means for associating an environment position in the three dimensional
environment with a folded vector that passes through the map origin, the folded vector
lying in a plane containing both the viewing direction vector and the environment

position and forming an angle with the viewing direction vector that is a predetermined function of the angle between the viewing direction vector and a vector between the map origin and the environment position;

5 means for associating an environment position with the map position corresponding to the direction of the folded vector associated with that environment position; and

means for deriving properties for a map position from the properties of the corresponding environment position.

10

14. An image rendering apparatus comprising:

map generating apparatus according to claim 13;

15 means for deriving a reflection vector, in respect of a point of interest on an object to be displayed, in dependence on a normal vector at the point of interest and a direction of view;

means for referencing a position in the two dimensional map using the reflection vector, to detect environmental properties at that map position; and

means for varying the appearance of the object at the point of interest in dependence on the detected environmental properties.

20

15. A video game machine comprising apparatus according to claim 13 or claim 14.